



SWE-400 LE

PROVEN, COST-EFFECTIVE, HIGH PERFORMANCE 400mm MULTI SENSOR SURVEILLANCE SYSTEM

- High Resolution Thermal and TV Sensors
- Continuous Zoom for Optimal Situational Awareness
- Options for Geo-Reference and Video Tracking
- Interfaces for Moving Map and Searchlight

GYRO STABILIZED GIMBAL

A fully digital 4-axis active gyro stabilization system compensates for aircraft movements and vibrations to provide stable imagery.

RELIABILITY AND LOW MASS

Gimbals are designed and manufactured using an aluminium structure combined with composite covers, to provide a reliable and lightweight solution.

ON-SCREEN GRAPHICS OPERATION

The operator is provided with comprehensive on-screen graphics information including camera look-angles, GPS coordinates, time and date etc.

ENVIRONMENTAL DESIGN

According to RTCA DO 160

IMU/INS FOR GEO-REFERENCE

Enabling accurate target geo-location and geo-hold.

NON-ITAR

Fully exportable in accordance with EU regulations



MULTI SENSOR SURVEILLANCE SYSTEM

The SWE-400 LE offers the largest capacity for sensor payloads in the SWE- range of gimbal systems. The 400mm fully digital 4-axis gyro-stabilized platform provides maximum flexibility for different sensor and lens combinations.

The SWE-400 LE can accommodate various payload options, including cooled thermal sensors, HD TV, colour spotter scope and lasers. Video target tracking, geo-location, and various laser rangefinders, illuminators and pointers are also available.



Additional Features

- Interface for remote control by third party devices
- Interface for slaving of searchlights
- Accurate geo-location, geo-hold and distance measurements of objects
- Advanced video auto tracking for robust tracking of moving or stationary objects
- Compatible with augmented reality moving map systems for full situational awareness

GIMBAL SPECIFICATIONS

Type	Four Axis Active Gyro Stabilized Gimbal
Coverage Azimuth	360° continuous
Coverage Elevation	+90° to -120°
Dimension	Ø 400 mm (15.7")
Weight	30kg (66lb)
Power	20-30VDC, 250W

TV SENSOR

Option	HD	SD
Type	Full HD 1080p	PAL/NTSC
Image Sensor	1/2.8" CMOS	Super HAD CCD (1/4")
Number of Pixels	≈ 2,380,000 Pixels	≈ 570,000 Pixels
Optical Zoom	30x (60° to 2°)	40x (60° to 1.6°)
Digital Zoom	Yes	Yes

THERMAL IMAGER

Detector	Cooled MCT
Array Size	640x512 pixels
Spectral Range	3-5µm
NETD	<25mK typical
Lens	Continuous zoom
Field of View	39° to 1.8° (HFOV)

Object	Detection	Recognition	Identification
Man	9.7 km	2.9 km	1.55 km
Vehicle	16.6 km	6.4 km	3.5 km

ACCESSORIES

Standard Configuration	Turret Camera Unit, Hand Controller Unit, Interface Unit, Cables
Other Options	IMU/INS, Lasers, Video Tracker, SLASS/ Moving Map Interface, Geo-Reference capabilities.
Installation Kits	Available for most helicopter types, please enquire



Trakka Corp Pty Ltd
 23 Kilpa Road, Moorabbin
 Victoria 3189 Australia
 Phone: +61 3 9553 3000

Trakka Systems AB
 Stationsvägen 46
 640 43 Ärla Sweden
 Phone: +46 16 708 60

Trakka USA LLC
 6817b Academy Parkway East NE
 Albuquerque New Mexico 87109 USA
 Phone: +1 505 345 0270