



SWE-300 TRIPLE

Cost-effective Imaging System with High Resolution Radiometric Infrared, Corona Detection and HD TV cameras.

GYRO STABILIZED GIMBAL

For stable, long range imaging, a fully digital 4-axis active gyro stabilization system compensates for aircraft maneuvering and eliminates external vibrations.

SUPERIOR PERFORMANCE THERMAL IR

High precision measurement accuracy, superb image quality and long-wave solar reflection immunity provide outstanding performance for applications requiring real time temperature readings.

THERMAL RADIOMETRIC OUTPUT

The radiometric output provides full thermal resolution images for temperature analysis and reporting.

CORONA DETECTION

The solar blind camera detects UV discharges in the full daylight.

GEO-REFERENCING/TRACKING

The IMU/INS combined with the laser rangefinder provides and holds the geographical locations of points of interest. The tracker locks the camera to any structure or scene.

RELIABILITY - ENVIRONMENTAL DESIGN

In order to ensure reliability, the gimbal is designed according to RTCA DO 160 standards.



FEATURES & APPLICATIONS

The SWE-300 Triple multi-sensor imaging system offers commercial users the capability to measure temperatures in real time, to detect Corona discharges and to collect high resolution video from an airborne platform. The systems can be fully integrated with geo-spatial recorders, mapping systems and reporting software to deliver comprehensive fault reports to industry users. The products are completely ITAR-free and are widely exportable.

Typical applications include:

- Powerline asset inspection
- Right of Way (ROW) surveys
- Storm damage assessment
- Pipeline inspection
- Agriculture monitoring
- Environmental surveys
- Animal surveys
- Forest fire fighting and mapping



SWE-300 Triple

- Three unique sensors combined into a compact camera platform
- Real time temperature measurements and radiometric temperature analysis
- Solar Blind UV detection camera
- High Definition TV video camera
- Geo-location and Geo-pointing
- Scene/Object tracking

PERFORMANCE SPECIFICATIONS

GIMBAL SYSTEM

Type	Four Axis Active Gyro Stabilized Gimbal
Stabilization	≈ 15 μRad
Coverage Az	360° continuous
Coverage El	+20° to -120°
Dimension	Ø 300 mm (11.8")
Weight	18kg (39lb)
Power	20-30VDC, 250W

DAYLIGHT TV CAMERA

Type	Full HD 1080p
Image Sensor	1/2.8" CMOS
Number of Pixels	≈ 2,380,000 Pixels
Optical Zoom	30x (60° to 2°)
Digital Zoom	Yes

THERMAL IR CAMERA

Array Size	1024x768 pixels
Lens	12°x16° (optional 24°x32°)
Detector	Microbolometer FPA
Spectral Range	7.5-14μm
Thermal Sensitivity	<0.05°K
Focus	Manual and Auto Focus
Digital Zoom	Yes
Temp Accuracy	+/-1.5°C, (+/-1.5% of reading)

CORONA UV CAMERA

Detector	UVc, Solar Blind
FOV	8°x6°
Spectral Range	250-280nm
Focus	Auto Focus
Features	Gain, Counting

ACCESSORIES

Standard Config	Turret Camera Unit, Hand Control Unit, Interface Unit, cable kit
Optional	Radiometric Package including thermal analysis and report generating Software IMU/INS and LRF for GEO reference capabilities Scene/Object Tracking
Installation Kit	Available for most helicopter types, please enquire



Trakka Corp Pty Ltd
23 Kilpa Road, Moorabbin
Victoria 3189 Australia
Phone: +61 3 9553 3000

Trakka Systems AB
Stationsvägen 46
640 43 Ärla Sweden
Phone: +46 16 708 60

Trakka USA LLC
6817b Academy Parkway East NE
Albuquerque New Mexico 87109 USA
Phone: +1 505 345 0270