



SWE-200 LE

Lightweight, Multi-Sensor Day & Night Imaging System.

Ideal for small aircraft, UAVs and vehicle installations.

4-AXIS GYRO STABILIZED GIMBAL

For stable, long range imaging, a fully digital 4-axis active gyro stabilization system compensates for platform maneuvering and eliminates external vibrations.

COMPACT AND LIGHTWEIGHT

The small size and low weight of the gimbal ensures minimal impact on the center-of-gravity, power draw, and mission endurance of the platform.

FLEXIBLE INSTALLATIONS

Trakka Systems works together with customers to provide flexible installation solutions to interface the gimbal to the aircraft, and fixed or mobile ground installations.

RELIABILITY – ENVIRONMENTAL DESIGN

In order to ensure reliability, the gimbal is designed according to RTCA DO 160 standards.

EXPORTABLE

Trakka camera systems are fully exportable in accordance with EU regulations.



TRAKKA SYSTEMS SWE-200 LE

The SWE-200 LE is a compact and lightweight dual-LRU multi-sensor surveillance system offering day and night mission capabilities. With a diameter of only 200mm, the SWE-200 LE provides a fully digital 4-axis gyro-stabilized platform making it the ideal choice for installation on aircraft or rotorcraft or vehicles where size and weight are challenging factors. The SWE-200 LE can accommodate various payload options, including thermal imagers, HD TV cameras as well as a laser rangefinder. Video auto tracking, geo-location, and various remote interface options are available.



SWE-200 LE

- Compact and lightweight
- High Resolution Day and Night Capabilities
- Uncompromised 4-axis Stabilization
- Geo-location and tracking
- Digital interface to mission equipment
- Exportable
- Operable as a single LRU

PERFORMANCE SPECIFICATIONS

GIMBAL SYSTEM

Type	Four Axis Active Gyro Stabilized Gimbal
Coverage Az	360° continuous
Coverage El	+90° to -120°
Diameter	Ø 200 mm (7.8")
Weight	6-8kg (13-17lb)
Power	22-30VDC, 150W

DAYLIGHT SENSOR

Option	HD	SD
Type	Full HD 1080p	PAL/NTSC
Image Sensor	1/2.8" CMOS	1/4" Super HAD CCD
Number of Pixels	≈ 2,380,000 Pixels	≈ 570,000 Pixels
Optical Zoom	30x (60° to 2°)	40x (60° to 1.6°)
Digital Zoom	Yes	Yes

THERMAL IMAGER

Detector	Uncooled Microbolometer
Array Size	640 x 512 Pixels
Spectral Range	7.5-13.5µm
Lens options	25, 35, 60mm

ACCESSORIES

Sensors	IMU/INS, Laser Rangefinder
Accessories	Hand Controller Unit, Interface Unit, Cables, Video Tracker, Search Light/Moving Map Interface



Trakka Corp Pty Ltd
 23 Kilpa Road, Moorabbin
 Victoria 3189 Australia
 Phone: +61 3 9553 3000

Trakka Systems AB
 Stationsvägen 46
 640 43 Ärla Sweden
 Phone: +46 16 708 60

Trakka USA LLC
 6817b Academy Parkway East NE
 Albuquerque New Mexico 87109 USA
 Phone: +1 505 345 0270