



## SWE-300 TRIPLE

**Cost-effective Imaging System with High Resolution Radiometric Infrared, Corona Detection and HD TV cameras.**

### **GYRO STABILIZED GIMBAL**

For stable, long range imaging, a fully digital 4-axis active gyro stabilization system compensates for aircraft maneuvering and eliminates external vibrations.

### **SUPERIOR PERFORMANCE THERMAL IR**

High precision measurement accuracy, superb image quality and long-wave solar reflection immunity provide outstanding performance for applications requiring real time temperature readings.

### **THERMAL RADIOMETRIC OUTPUT**

The radiometric output provides full thermal resolution images for temperature analysis and reporting.

### **CORONA DETECTION**

The solar blind camera detects UV discharges in the full daylight.

### **GEO-REFERENCING/TRACKING**

The IMU/INS combined with the laser rangefinder provides and holds the geographical locations of points of interest. The tracker locks the camera to any structure or scene.

### **RELIABILITY - ENVIRONMENTAL DESIGN**

In order to ensure reliability, the gimbal is designed according to RTCA DO 160 standards.



### **FEATURES & APPLICATIONS**

The SWE-300 Triple multi-sensor imaging system offers commercial users the capability to measure temperatures in real time, to detect Corona discharges and to collect high resolution video from an airborne platform. The systems can be fully integrated with geo-spatial recorders, mapping systems and reporting software to deliver comprehensive fault reports to industry users. The products are completely ITAR-free and are widely exportable.

#### **Typical applications include:**

- Powerline asset inspection
- Right of Way (ROW) surveys
- Storm damage assessment
- Pipeline inspection
- Agriculture monitoring
- Environmental surveys
- Animal surveys
- Forest fire fighting and mapping



## SWE-300 Triple

- Three unique sensors combined into a compact camera platform
- Real time temperature measurements and radiometric temperature analysis
- Solar Blind UV detection camera
- High Definition TV video camera
- Geo-location and Geo-pointing
- Scene/Object tracking

## PERFORMANCE SPECIFICATIONS

### GIMBAL SYSTEM

Type	Four Axis Active Gyro Stabilized Gimbal
Stabilization	≈ 15 μRad
Coverage Az	360° continuous
Coverage El	+20° to -120°
Dimension	Ø 300 mm (11.8")
Weight	18kg (39lb)
Power	20-30VDC, 250W

### DAYLIGHT TV CAMERA

Type	Full HD 1080p
Image Sensor	1/2.8" CMOS
Number of Pixels	≈ 2,380,000 Pixels
Optical Zoom	30x (60° to 2°)
Digital Zoom	Yes

### THERMAL IR CAMERA

Array Size	1024x768 pixels
Lens	12°x16° (optional 24°x32°)
Detector	Microbolometer FPA
Spectral Range	7.5-14μm
Thermal Sensitivity	<0.05°K
Focus	Manual and Auto Focus
Digital Zoom	Yes
Temp Accuracy	+/-1.5°C, (+/-1.5% of reading)

### CORONA UV CAMERA

Detector	UVc, Solar Blind
FOV	8°x6°
Spectral Range	250-280nm
Focus	Auto Focus
Features	Gain, Counting

## ACCESSORIES

Standard Config	Turret Camera Unit, Hand Control Unit, Interface Unit, cable kit
Optional	Radiometric Package including thermal analysis and report generating Software IMU/INS and LRF for GEO reference capabilities Scene/Object Tracking
Installation Kit	Available for most helicopter types, please enquire



**Trakka Corp Pty Ltd**  
23 Kilpa Road, Moorabbin  
Victoria 3189 Australia  
Phone: +61 3 9553 3000

**Trakka Systems AB**  
Stationsvägen 46  
640 43 Ärla Sweden  
Phone: +46 16 708 60

**Trakka Systems USA LLC**  
4725 Lena Road, Unit 103  
Bradenton Florida 34211, USA  
Phone: +1 941 500-5158